

표준소비효율(고효율) 배전용 변압기 Distribution Transformer

Ratings





Phase : Three, Single

Frequency: 50Hz, 60Hz

High Voltage: 22.9kV, 6.6kV, 3.3kV

Low Voltage: 220, 380, 440, 480, 220Y/127, 380Y/220, 400Y/230, 440Y/254, 480Y/277

Vector: Dd0, Dyn11, etc



최저소비효율 (22900V - LV)

Capacity (Kva)	ξ (%)	ϵ (%)	l_o (%)	Dimensions(mm)			OIL (ℓ)	weight (kg)
				W	D	H		
100	99.00	1.9	6.0	1220	740	1400	350	1130
200	99.10	1.7	5.5	1290	810	1420	390	140
250	99.20	1.7	5.5	1360	830	1440	440	1650
300	99.20	1.6	5.0	1360	830	1440	440	1650
400	99.25	1.6	4.5	1510	1000	1540	530	2000
500	99.25	1.5	4.5	1490	1000	1560	525	2090
600	99.30	1.5	4.5	1610	1070	1560	625	2485
750	99.30	1.4	4.0	1640	1100	1600	710	2790
800	99.30	1.4	4.0	1640	1100	1600	710	2800
900	99.35	1.4	4.0	1730	1170	1640	815	3380
950	99.35	1.4	4.0	1760	1180	1640	840	3470
1000	99.35	1.4	4.0	1790	1190	1640	870	3560

6600V ~ 3300V - LV

Capacity (Kva)	ξ (%)	ϵ (%)	l_o (%)	dimensions(mm)			OIL (ℓ)	weight (kg)
				W	D	H		
100	99.00	1.9	6.0	1220	740	1400	340	1080
200	99.10	1.7	5.5	1290	810	1420	380	1340
250	99.20	1.7	5.5	1360	830	1440	430	1570
300	99.20	1.6	5.0	1360	830	1440	430	1570
400	99.25	1.6	4.5	1510	1000	1540	520	1900
500	99.25	1.5	4.5	1490	1000	1560	515	1990
600	99.30	1.5	4.5	1610	1070	1560	615	3270
750	99.30	1.4	4.0	1640	1100	1600	700	2650
800	99.30	1.4	4.0	1640	1100	1600	700	2670
900	99.35	1.4	4.0	1730	1170	1640	805	3220
950	99.35	1.4	4.0	1760	1180	1640	830	3300
1000	99.35	1.4	4.0	1790	1190	1640	860	3390